

# BeneHeart C2

## Automated External Defibrillator (AED)



### Defibrillator

Operations	Semi-automatic and fully automatic versions
Waveform	Biphasic Truncated exponential (BTe), with automated voltage and duration compensation for patient impedance
Range of selected energy	100 to 360 J (adult) 10 to 100 J (child)
Energy default	200-300-360 J (adult) 50-70-100 J (child) Default configuration meets AHA/ERC Guidelines 2015.
Energy accuracy	±2 J or ±10 % of setting, whichever is greater
Power on time	< 2 seconds
ECG analysis time	< 5 seconds
Charge time	0 seconds (as device is pre-charged during ECG analysis)
Time from power on to shock ready	< 8 seconds (200J, new battery, 20±5°C)
Mindray shockable rhythm analysis algorithm	Acquires and analyzes the patient's ECG signals to determine whether or not to give a defibrillation shock
Sensitivity and specificity	Meets AAMI DF80 specifications and IEC 60601-2-4 specifications
Patient impedance range	25 to 300 Ω

### User Prompts

User prompts	On-screen text and animation prompts, voice prompts
CPR coaching	Animation and voice guide CPR metronome CPR real-time feedback <sup>1</sup>
CPR protocol	Meets AHA/ERC Guidelines 2015 and/or can be configured locally

### Controls

Lid release/ON-OFF	Controls device power on/off
Shock button	Delivers energy when button is pressed by the user (semi-automatic only)
Adult/child mode switch	Switch to child mode for reduced energy and appropriate CPR guidance

Language button	Optional feature allows the user to switch between max. 3 languages
-----------------	---

### Physical Characteristics

Dimension	210 mm (w) x 286 mm (d) x 78 mm (h)
Weight	2.3 kg (including one battery)

### Display

Type	TFT Color LCD
Dimensions	7 inch
Resolution	800 × 480 pixels

### Environmental

Dust/water resistance	IP55
Temperature	Operating: -5 to 50 °C Short-term storage: -30 to 70 °C for a maximum of 7 days Long-term storage: 15 to 35°C
Humidity	Operating/storage: 5 to 95 % (non-condensing)
Altitude	Operating/storage: -381 m to +4575 m
Shock	RTCA-DO-160G-2010, Section 7 IEC60601-1-12, 10.1.3, 10.1.4
Vibration	MIL-STD-810G-2008, method 514.6, Category 13, Category 14, Category 20, Category 24 EN13718-1, 4.7.2
Bump	EN1789, 6.3.4.2 EN13718-1, 4.7.2
Drop	1.5 m
EMC	IEC60601-1-2: 2014 EN13718-1, 4.5.7 IEC 60601-1-12, 11

### Battery

Type	Lithium manganese dioxide (Li/MnO <sub>2</sub> ), disposable, 4200 mAh
Standby life	6 years (at 20±5 °C, performing auto test every week, not in use, not sending self-test report) 5 years (at 20±5 °C, performing auto test every day, not in use, not sending self-test report)

<b>Capacity</b>	<b>With new battery at 20±5 °C: ≥ 12 hours of operating times; provides 350 shocks @200J (3 shocks in 1 minute)</b>
<b>Replace battery indication</b>	<b>Min. 10 shocks at 200 J and 30 minutes of operating time (at 20±5 °C, typical).</b>
<b>Weight</b>	<b>300 g</b>

#### **Electrode Pads**

<b>Type</b>	<b>Pre-connected, disposable, for adult/child</b>
<b>Shelf life</b>	<b>5 years (from date of manufacture)</b>

#### **CPR Sensor<sup>2</sup>**

<b>Weight</b>	<b>Approximately 180 g (without battery)</b>
<b>Thickness</b>	<b>17.5 to 19 mm</b>

#### **Automatic Self-test**

<b>Auto-test</b>	<b>Daily, weekly, monthly, quarterly</b>
<b>Status indicator</b>	<b>Visual indicators indicating system readiness</b>

#### **Data Storage**

<b>Events</b>	<b>Up to 500 events</b>
<b>Voice recording</b>	<b>Up to 1 hour</b>
<b>CPR data</b>	<b>Up to 5 hours</b>
<b>Self-test reports</b>	<b>1000 records</b>
<b>Data export</b>	<b>Through USB flash memory</b>

#### **Communications**

<b>Wireless data transfer to AED-Alert™ 2.0 system</b>	<b>Through 5G/2.4G Wi-Fi or cellular (4G)<sup>3</sup> network</b>
--	---

<sup>1</sup> Requiring to configure with CPR sensor

<sup>2</sup> For further information about the availability of CPR sensor, please contact with your local sales representatives.

<sup>3</sup> For further information about the availability of 4G data transfer and AED-Alert™ 2.0 system, please contact with your local sales representatives.

[www.mindray.com](http://www.mindray.com)

P/N:ENG-C2 Datasheet -210285X2P-20190830

©2019 Shenzhen Mindray Bio-Medical Electronics Co.,Ltd. All rights reserved.

**mindray**  
healthcare within reach

